

**产品规格书****Specification of Product**

产品名称: 7.4V 18公斤 串行总线舵机
 Product Name: 7.4V 18kg.cm Serial Control BUS Servo

产品型号 Model No. SCS215

1. 使用环境条件 Apply Environmental Condition

No.	Item	Specification
1-1	存储温度 Storage Temperature Range	-30°C~80°C
1-2	运行温度 Operating Temperature Range	-15°C~70°C

2. 测试环境 Standard Test Environment

No.	Item	Specification
2-1	温度 Temperature range	25°C ±5°C
2-2	湿度 Humidity range	65%±10%

3. 机械特性 Mechanical Specification

No.	Item	Specification
3-1	尺寸 Size	A: 45.2mm B: 24.7mm C: 35mm
3-2	重量 Weight	52g ±0.2
3-3	齿轮类型 Gear type	Metal Gear(345:1)
3-6	机构极限角度 Limit angle	No limit
3-7	轴承 Bearing	2 Ball bearings
3-8	出力轴 Horn gear spline	25T
3-9	摆臂 Horn type	Plastic,POM
3-10	外壳 Case	engineering plastic
3-11	舵机线 Connector wire	200mm ±5 mm
3-12	马达 Motor	core motor
3-13	防水性能 Splash water resistance	NO

4. 电气特性 Electrical Specification (Function of the Performance)

No.	工作电压 Operating Voltage Range	6V	7.4V
4-1*	静态电流 Idle current (at stopped)	5mA	6mA
4-2*	空载速度 No load speed	0.16sec/60°	0.14sec/60°
4-3*	空载电流 Running current (at no load)	130 mA	150 mA
4-4	堵转扭矩 Peak stall torque	17kg.cm	19.5kg.cm
		236.1oz.in	270.8oz.in
4-5	堵转电流 Stall current	2000 mA	2500mA

Note: "*"definition is average value when the servo running with no load

产品名称: 7.4V 18公斤 串行总线舵机
 Product Name: 7.4V 18kg.cm Serial Control BUS Servo

产品型号 Model No. SCS215

5. 控制特性 Control Specification:

No.	Item	Specification
5-1	控制信号 Command signal	Bus Packet Communication TTL level
5-2	协议类型 Protocol Type	Half duplex Asynchronous Serial Communication
5-3	ID范围 ID range	0-253
5-4	通读速率 Communication Speed	38400bps ~ 1 Mbps
5-5	旋转角度 Running degree	300° (when 0~1023)
5-6	反馈 Feedback	Load, Speed, Input Voltage
5-7	位置传感器分辨率 Position Sensor (Resolution)	Potentiometer (300° /1024)

6. 外形图 The Drawings
