

**产品规格书****Specification of Product**

产品名称: 6V 1.5kg PWM 360° 连续转数码舵机

Product Name: 6V 1.5kg.cm PWM 360° Continuous rotation Digital Servo

产品型号 Model No. FT90R

1. 使用环境条件 Apply Environmental Condition

No.	Item	Specification
1-1	存储温度 Storage Temperature Range	-30℃~80℃
1-2	运行温度 Operating Temperature Range	-10℃~70℃

2. 测试环境 Standard Test Environment

No.	Item	Specification
2-1	温度 Temperature range	25℃ ±5℃
2-2	湿度 Humidity range	65%±10%

3. 机械特性 Mechanical Specification

No.	Item	Specification
3-1	尺寸 Size	A: 22.9mm B: 12.1mm C: 26.5mm
3-2	重量 Weight	9g
3-3	齿轮类型 Gear type	Plastic Gear
3-6	机构极限角度 Limit angle	360°
3-7	轴承 Bearing	NO Ball bearings
3-8	出力轴 Horn gear spline	20T
3-9	摆臂 Horn type	Plastic, POM
3-10	外壳 Case	ABS
3-11	舵机线 Connector wire	250mm ±5 mm JR
3-12	马达 Motor	Metal brush motor
3-13	防水性能 Splash water resistance	NO

4. 电气特性 Electrical Specification (Function of the Performance)

No.	工作电压 Operating Voltage Range	4.8V	6V
4-1*	静态电流 Idle current (at stopped)	5mA	6mA
4-2*	空载速度 No load speed	110RPM	130RPM
4-3*	空载电流 Runnig current (at no load)	100 mA	120 mA
4-4	堵转扭矩 Peak stall torque	1.3kg.cm	1.5kg.cm
		18.09oz.in	20.86oz.in
4-5	堵转电流 Stall current	800 mA	900mA

Note: "*"definition is average value when the servo runing with no load

产品名称: 6V 1.5kg PWM 360° 连续转数码舵机

Product Name: 6V 1.5kg.cm PWM 360° Continuous rotation Digital Servo

产品型号 Model No. FT90R

5. 控制特性 Control Specification:

No.	Item	Specification
5-1	控制信号 Command signal	Pulse width modification
5-2	放大器类型 Amplifier type	Digital Controller
5-3	脉冲宽度范围 Pulse width range	900~2100 μ sec
5-4	停止位置 Neutral position	1500 μ sec
5-5	旋转角度 Running degree	360°
5-6	死区宽度 Dead band width	$\pm 20\mu$ sec
5-7	旋转方向 Rotating direction	CW(1500~1000 μ sec), CCW(1500~2000 μ sec)

6. 外形图 The Drawings

