



产品名称: 6V 4.5公斤 磁编码360度串行总线舵机 Product Name: 6V 4.5kg magnetically coded 360-degree serial bus servo
产品型号 Model No. STS3032-C001

1. 使用环境条件 Apply Environmental Condition

No.	Item	Specification
1-1	存储温度 Storage Temperature Range	-30℃~80℃
1-2	运行温度 Operating Temperature Range	-15℃~70℃

2. 测试环境 Standard Test Environment

No.	Item	Specification
2-1	温度 Temperature range	25℃ ±5℃
2-2	湿度 Humidity range	65%±10%

3. 机械特性 Mechanical Specification

No.	Item	Specification
3-1	尺寸 Size	A: 23.2mm B: 12.1mm C: 28.5mm
3-2	重量 Weight	20g ±0.2
3-3	齿轮类型 Gear type	Metal Gear
3-6	机构极限角度 Limit angle	无限制
3-7	轴承 Bearing	2 Ball bearings
3-8	出力轴 Horn gear spline	25T
3-9	摆臂 Horn type	Plastic, POM
3-10	外壳 Case	铝合金
3-11	舵机线 Connector wire	200mm ±5 mm
3-12	马达 Motor	空心杯马达
3-13	传感器 sensor	磁编码

4. 电气特性 Electrical Specification (Function of the Performance)

No.	工作电压 Operating Voltage Range	4.8V	6V
4-1*	静态电流 Idle current (at stopped)	4.8mA	6mA
4-2*	空载速度 No load speed	0.1sec/60°	0.09sec/60°
4-3*	空载电流 Running current (at no load)	125 mA	150 mA
4-4	堵转扭矩 Peak stall torque	4kg. cm	4.5kg. cm
		55.65oz. in	62.6oz. in
4-5	堵转电流 Stall current	900mA	1200mA

Note: "*"definition is average value when the servo running with no load



产品名称: 6V 4.5公斤 磁编码360度串行总线舵机

Product Name: 6V 4.5kg magnetically coded 360-degree serial bus servo

产品型号 Model No. STS3032-C001

5. 控制特性 Control Specification:

No.	Item	Specification
5-1	控制信号 Command signal	总线数据包TTL电平
5-2	协议类型 Protocol Type	半双工异步通信
5-3	ID范围 ID range	0-253
5-4	通读速率 Communication Speed	38400bps ~ 1 Mbps
5-5	旋转角度 Running degree	360° (when 0~4096)
5-6	反馈 Feedback	位置、温度、速度、电压、负载
5-7	位置传感器分辨率 Position Sensor (Resolution)	Potentiometer (360° /4096)

6. 外形图 The Drawings

